


# LVC-5000N4

**Fanless Mobile NVR with Intel 847E / i7-2655LE series featuring 4 PoE Ports for Transport Surveillance**



## Features

### Multiple PoE LAN ports to support Transport Surveillance

This mobile NVR with 4 PoE ports (IEEE 802.3af) is suitable for IP Video Surveillance and real-time recording applications.

### Designed for MIL-STD-810G with Extreme Vibration Resistance

LVC-5000N4 series is in compliance with MIL-STD-810G vibration and shock standards and includes SSD storage and a Suspension Kit to further improve robustness.

### Fanless Design with Corrugated Aluminum

The corrugated aluminum casing lets heat dissipate through the top of the device, allowing for a fanless design.

### Convenient DC output

The LVC-5000N4 series offers 12VDC Output (max 1A) for external devices, operational in concert with the Ignition Power Management feature.

### Vehicle Ignition Power Management

Detects vehicle ignition on/off status and allows flexible control of the delay time via software utility.

## Modularized and customizable design

The LVC-5000N4 series design features the Lanner Proprietary Internal Multi-I/O Interface, which carries signals for 2 USB ports, 4 x UART, 4 x Digital I/O, 2 x PCIe, and 1 x SATA 2.0. This allows for customized add-on modules for other features.

## Key lock for Drive Bay

The system is with key lock for removable drive bay.


## Settings and Installation via the front panel

MCU setting and CF card and SIM card installation is easy to access simply by opening the front panel.

## Multi I/O

The MIO design includes 12V Level GPIO, audio, MCU TX/RX and also includes 2x DI (Digital Input from MCU) which can connect sensors to detect the environment. Once defined events occur, the LVC-5000N4 can be turned on automatically.

**Dimensions: 273.8 x 64.8 x 188 mm (10.78" x 2.55" x 7.4" )**



## Preliminary Specifications

<b>Dimensions (WxHxD)</b>		273.8 x 64.8 x 188 mm (10.78" x 2.55" x 7.4" )
<b>Processor</b>		Intel 847E/i7-2655LE Processors
<b>Chipset</b>		Intel HM65
<b>System Memory</b>	Technology	DDR3 SO-DIMM x1 ( Factory default: 4GB module pre-installed )
	Max. Capacity	Up to 8GB
<b>Storage</b>	SATA/CF	Removable 2.5" SSD/HDD drive bay x1 for LVC-5000N4, CF socket x1
<b>Ethernet Controller</b>		Intel 82583V x4
<b>Graphic Controller</b>		Intel integrated HD graphic engine
<b>Audio Controller</b>		Realtek ALC886 HD codec
<b>IO</b>	LAN	GbE RJ45 x4
	Display	DVI-D, maximum resolution up to 1920x1200@75Hz VGA, maximum resolution up to 2048x1536@60Hz HDMI, maximum resolution up to 1920x1200@75Hz
		Dual display function supports Independent, clone and extended mode.(VGA+DVI or VGA+HDMI)
	Audio	Mic-in and Line-out with 2 watt by terminal block MIO connector
	Serial I/O	1x RS-232 and 1x RS-232/422/485 both with RI/5V/12V
	GPS	Ublox NEO-6Q GPS receiver module
	G-sensor	ADXL 345
	GPIO	4x DI and 4xDO with 5V/12V Level by jumper setting 2x DI (from MCU) 3.3V Level 2x DO control relay with contact current @ 2A
		USB 2.0
	Power Input	3-pin terminal block (+, -, ignition)
	Expansion	Mini-PCIe x2 (Both with SIM card reader)
	PoE	PoE x4, IEEE 802.3af, Standard PoE
	Others	External: 4x SMA antenna hole, Remote Power switch Internal: Lanner Proprietary MIO
	<b>Power Input</b>	
<b>PoE Power Module</b>		Internal integrated
<b>OS Support</b>		Linux: Redhat Enterprise 5/ Fedora 14. Linux Kernel 2.6.18 or later Windows: XP embedded ; Win7 Pro FES/Embedded; Win8
<b>Certifications</b>		CE, FCC Class A, E13, RoHS
<b>Compliance</b>		Vibration: MIL-STD-810G, Method 514.6 Shock:MIL-STD-810G, Method 516.6
<b>Operating Temperature Range</b>	Extended	With Selected Industrial Components -20~55°C/-4~131°F
	Standard	With Commercial Components -5~45°C / 23~113°F

## Ordering Information

<b>LVC-5000N4-7A</b>	Intel® i7-2655LE In-Vehicle Mobile NVR Computer, 4GB DDR3 Memory included, 2.5" Removable Drive Bay, Mini-PCIe x2 with two SIM card reader, Intel GbE x4 with PoE support, USB x4, COM x2, MIO, Audio, HDMI, DC Power input +9~36Vdc with Ignition, Suspension Kit included.
<b>LVC-5000N4</b>	Intel® 847E In-Vehicle Mobile NVR Computer, 4GB DDR3 Memory included, 2.5" Removable Drive Bay, Mini-PCIe x2 with two SIM card reader, Intel GbE x4 with PoE support, USB x4, COM x2, MIO, Audio, HDMI, DC Power input +9~36Vdc with Ignition, Suspension Kit included.